



100% ACRYLIC MILDEW & STAIN RESISTANT FINISH

FLOOR & DECK H2O

INSECO FLOOR & DECK H2O is a versatile and durable coating which produces a hard, tough, protective finish. FLOOR & DECK H2O exhibits excellent adhesion, hot tire resistance, easy application and maximum performance on both wood and concrete floors.

Always test for adhesion

2 thin coats recommended

200-300 sqft coverage/gal

Concrete and wood

DO NOT FREEZE



HAGA CLIC AQUÍ PARA ESPAÑOL

RECOMMENDED USES: For properly prepared concrete patios, walkways, pool decks, asphalt, driveways, garage floors, wood decks and composite decking. For interior and exterior use. Do not apply to smooth troweled concrete floors without proper preparation. A texture is required for sufficient adhesion.

SURFACE PREPARATION: General: Dirt, grease, grime and any foreign material must be removed before application of new coating. Treat surface for mildew. Ensure surface is clean and dry. Contact an Inseco representative for detailed surface preparation specifications. **New or unpainted concrete:** Dirt, grease, grime and any foreign material must be removed before application of new coating. Apply a solution of 1 part muriatic acid to 4 parts water then thoroughly wash with a TSP solution or a powerful degreasing detergent. Smooth troweled floors must be etched until pores are open and a texture is achieved. Pressure washing is highly recommended to ensure all contaminants are removed. Apply two coats FLOOR & DECK H2O.

Painted surfaces: FLOOR & DECK H2O will adhere to most prepainted surfaces that are firmly bonded to the substrate. Dirt, grease, grime and any foreign material must be removed before application of new coating. Do not acid etch previously painted surfaces. FLOOR & DECK H2O may not be compatible with certain types of existing finishes. Glossy surfaces should be lightly sanded prior to application. Always check for adhesion prior to coating prepainted surfaces. **Stamped concrete:** Sandblasting is highly recommended for stamped concrete surfaces. Adhesion issues are common with stamped concrete surfaces. Contact an INSECO representative for detailed surface preparation specifications. **Unpainted wood surfaces:** Dirt, grease, grime and any foreign material must be removed before application of new coating. FLOOR & DECK H2O is self-priming. 2 Coats are recommended. New wood is susceptible to tannin staining. Should this occur, apply a stain blocking primer between coats of FLOOR & DECK H2O. **Composite decking:** Contact an INSECO representative for detailed specifications pertaining to the type of composite decking.

APPLICATION INFORMATION: Mix product thoroughly. Apply with brush roller or airless spray. Apply when surface temperatures are at least 50 deg. and rising. Do not thin with paint thinners. When spraying, use a tip designed for flat wall coatings.

CLEAN UP: Clean up drips and spills immediately using a damp cloth. Clean tools and equipment with soap and fresh water.

RECOMMENDED THINNER: FLOOR & DECK H2O does not require thinning and should be used as is, directly from the container.

COVERAGE (THEORETICAL): Coverage will depend on porosity and contour of the surface being coated. Coverage typically averages 200-300 square feet per gallon.

Finish:	Satin
Pigment Type:	Titanium Dioxide and inert pigments
Vehicle Type:	100% Acrylic Copolymer
Solvent Type:	Water
% Solids By Weight:	45% +/- 2%
% Solids By Volume:	35% +/- 2%
Density:	10.29 lbs. Per gallon
Viscosity @ 75 deg. F (24 deg. C):	100 +/- 2 K.U.
Coating VOC:	<200 g/l
Flash Point, Minimum:	Not Flammable
Flame Spread:	Class A rating on non-combustible substratum Recommended Dry Film
Thickness Per Coat:	1.0-2.0 MILS DFT.
Estimated Dry Time: High humidity and/or low temperatures may extend drying and curing time.	Touch: 30-60 Minutes Recoat: 2-4 Hours Foot Traffic: 12 Hours Vehicular Traffic: 72 Hours

DO NOT FREEZE! FLOOR & DECK H2O is waterbased

CAUTION: KEEP OUT OF REACH OF CHILDREN! WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear an NIOSH-approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Technical data contained herein is true and accurate at the date of issue, but is subject to change without notice. An Inseco representative should be contacted with any questions concerning product information or application procedures. Our products conform to Inseco quality standards, but no other warranty is expressed or implied. Liability, if any, is limited to the replacement of product or purchase price.



INSECO

INSECO Inc.
2897 South Street
Fort Myers, FL 33916

insecoproducts.com
(800) 883-5150
info@insecoproducts.com